

# Aggregate Optimization Chart

**PLANT #:** **P-102**

Sample Date: 6/8/20 Concrete Grade: **P1M**  
 Dates Test Represents: 6/9/2020 through 6/15/2020

Contractor: \_\_\_\_\_

MDOT No.: \_\_\_\_\_

Agg. Class	Pit #	Source	Weight (SSD)	ft <sup>3</sup>	Specific Gravity	% Contribution
CA	58-003	Stoneco	1420	8.46	2.69	45.5
IA	58-003	Stoneco	500	2.98	2.69	16.0
2NS	63-114	Highland	1200	7.26	2.65	38.5
<b>Total Wt</b>			<b>3120</b>	<b>18.70</b>		<b>100.0</b>

<----- Verify this number is 100%




**Superior Materials, LLC**  
 30701 W. 10 Mile Rd.  
 Suite 500  
 Farmington Hills, MI 48336

Sieve	CA	IA	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	67.7	100.0	100.0	85.3	14.7	14.7
3/4"	40.0	100.0	100.0	72.7	12.6	27.3
1/2"	19.1	89.4	100.0	61.5	11.2	38.5
3/8"	11.7	80.4	100.0	56.7	4.8	43.3
#4	4.4	24.5	99.0	44.0	12.7	56.0
#8	2.8	4.3	84.1	34.3	9.7	65.7
#16	2.2	1.3	66.7	26.9	7.4	73.1
#30	2.0	0.8	46.8	19.0	7.8	81.0
#50	1.8	0.7	17.1	7.5	11.5	92.5
#100	1.7	0.6	2.9	2.0	5.5	98.0
LBW	1.6	0.5	0.3	0.9	1.1	99.1

\*Maximum % Retained must be above the 3/8" sieve.  
 \*Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.  
 \*% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.  
 \*% Retained must be at least 8% for the 1" sieve when a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation  Batch Plant Gradations  Aggregate Supplier Gradations

<b>Coarseness Factor:</b>	<b>66</b>	<b>Workability Factor:</b>	<b>34</b>
---------------------------	-----------	----------------------------	-----------



Initial Production Sample (IPS)

<b>Coarseness Factor:</b>	<b>67</b>		
<b>Workability Factor:</b>	<b>35</b>		
Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	85.5	14.5	14.5
3/4"	73.4	12.1	26.6
1/2"	61.0	12.4	39.0
3/8"	56.2	4.8	43.8
#4	43.1	13.1	56.9
#8	34.9	8.2	65.1
#16	29.4	5.5	70.6
#30	21.6	7.8	78.4
#50	8.1	13.4	91.9
#100	2.2	5.9	97.8
LBW	1.4	0.8	98.6

PREPARED BY:  
 SM, LLC Technical Service

Approved By:

# Aggregate Optimization Chart

**PLANT #:** **P-12**

Sample Date: **6/8/20**

Concrete Grade: **P1M**

Contractor: \_\_\_\_\_

Dates Test Represents: **6/9/2020** through **6/15/2020**

MDOT No.: \_\_\_\_\_

Agg. Class	Pit #	Source	Weight (SSD)	ft <sup>3</sup>	Specific Gravity	% Contribution
CA	71-47	Presque Isle	900	5.50	2.62	29.3
IA	71-47	Presque Isle	920	5.63	2.62	30.0
2NS	63-115	Ray Rd	1250	7.56	2.65	40.7
<b>Total Wt</b>			<b>3070</b>	<b>18.69</b>		<b>100.0</b>

<----- Verify this number is 100%




**Superior Materials, LLC**  
 30701 W. 10 Mile Rd.  
 Suite 500  
 Farmington Hills, MI 48336

Sieve	CA	IA	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	96.1	100.0	100.0	98.9	1.1	1.1
1"	42.9	100.0	100.0	83.3	15.6	16.7
3/4"	11.6	97.8	100.0	73.4	9.8	26.6
1/2"	4.1	71.1	100.0	63.2	10.2	36.8
3/8"	3.2	44.2	100.0	54.9	8.3	45.1
#4	2.4	7.7	98.4	43.1	11.8	56.9
#8	2.2	3.3	79.8	34.1	9.0	65.9
#16	2.0	2.4	61.9	26.5	7.6	73.5
#30	1.9	2.2	46.2	20.0	6.5	80.0
#50	1.8	1.9	24.7	11.2	8.9	88.8
#100	1.7	1.8	5.3	3.2	8.0	96.8
LBW	1.4	1.4	0.5	1.0	2.2	99.0

\*Maximum % Retained must be above the 3/8" sieve.  
 \*Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.  
 \*% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.  
 \*% Retained must be at least 8% for the 1" sieve when a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation  Batch Plant Gradations  Aggregate Supplier Gradations

<b>Coarseness Factor:</b>	<b>68</b>	<b>Workability Factor:</b>	<b>34</b>
---------------------------	-----------	----------------------------	-----------



Initial Production Sample (IPS)

<b>Coarseness Factor:</b>	<b>67</b>
<b>Workability Factor:</b>	<b>35</b>

Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	99.6	0.4	0.4
1"	83.9	15.7	16.1
3/4"	74.0	9.8	26.0
1/2"	63.7	10.3	36.3
3/8"	56.4	7.3	43.6
#4	43.0	13.4	57.0
#8	35.1	7.9	64.9
#16	29.0	6.1	71.0
#30	20.9	8.0	79.1
#50	8.1	12.8	91.9
#100	1.6	6.5	98.4
LBW	0.9	0.8	99.1

PREPARED BY:  
 SM, LLC Technical Service

Approved By:

# Aggregate Optimization Chart

**PLANT #:** **P-32**

Sample Date: 6/8/20

Concrete Grade: **P1M**

Contractor: \_\_\_\_\_

Dates Test Represents: 6/9/2020 through 6/15/2020

MDOT No.: \_\_\_\_\_

Agg. Class	Pit #	Source	Weight (SSD)	ft <sup>3</sup>	Specific Gravity	% Contribution
CA	71-47	Presque Isle	870	5.32	2.62	28.3
IA	71-47	Presque Isle	950	5.81	2.62	30.9
2NS	95-013	Smelter Bay	1250	7.56	2.65	40.7
<b>Total Wt</b>			<b>3070</b>	<b>18.69</b>		<b>100.0</b>

<----- Verify this number is 100%




**Superior Materials, LLC**  
 30701 W. 10 Mile Rd.  
 Suite 500  
 Farmington Hills, MI 48336

Sieve	CA	IA	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	96.1	100.0	100.0	98.9	1.1	1.1
1"	42.9	100.0	100.0	83.8	15.1	16.2
3/4"	11.6	97.8	100.0	74.3	9.6	25.7
1/2"	4.1	71.1	100.0	63.9	10.4	36.1
3/8"	3.2	44.2	100.0	55.3	8.6	44.7
#4	2.4	7.7	96.1	42.2	13.1	57.8
#8	2.2	3.3	83.3	35.6	6.6	64.4
#16	2.0	2.4	69.3	29.5	6.0	70.5
#30	1.9	2.2	46.8	20.3	9.3	79.7
#50	1.8	1.9	18.5	8.6	11.6	91.4
#100	1.7	1.8	4.5	2.9	5.8	97.1
LBW	1.4	1.4	1.0	1.2	1.6	98.8

\*Maximum % Retained must be above the 3/8" sieve.  
 \*Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.  
 \*% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.  
 \*% Retained must be at least 8% for the 1" sieve when a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation  Batch Plant Gradations  Aggregate Supplier Gradations

**Coarseness Factor:** **69**      **Workability Factor:** **36**



Initial Production Sample (IPS)

**Coarseness Factor:** **65**  
**Workability Factor:** **35**

Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	99.4	0.6	0.6
1"	84.0	15.3	16.0
3/4"	73.5	10.5	26.5
1/2"	65.2	8.2	34.8
3/8"	58.2	7.1	41.8
#4	44.1	14.1	55.9
#8	35.5	8.6	64.5
#16	29.1	6.4	70.9
#30	21.9	7.3	78.1
#50	9.6	12.2	90.4
#100	2.6	7.1	97.4
LBW	1.0	1.6	99.0

PREPARED BY:  
 SM, LLC Technical Service

Approved By:

# Aggregate Optimization Chart

**PLANT #:** **P-36**

Sample Date: **6/8/20**

Concrete Grade: **P1M**

Contractor: \_\_\_\_\_

Dates Test Represents: **6/9/2020** through **6/15/2020**

MDOT No.: \_\_\_\_\_

Agg. Class	Pit #	Source	Weight (SSD)	ft <sup>3</sup>	Specific Gravity	% Contribution
CA	71-47	Presque Isle	870	5.32	2.62	28.3
IA	71-47	Presque Isle	1000	6.12	2.62	32.6
2NS	63-92	Grange Hall	1200	7.26	2.65	39.1
<b>Total Wt</b>			<b>3070</b>	<b>18.70</b>		<b>100.0</b>

<----- Verify this number is 100%




**Superior Materials, LLC**  
 30701 W. 10 Mile Rd.  
 Suite 500  
 Farmington Hills, MI 48336

Sieve	CA	IA	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	96.1	100.0	100.0	98.9	1.1	1.1
1"	42.9	100.0	100.0	83.8	15.1	16.2
3/4"	11.6	97.8	100.0	74.2	9.6	25.8
1/2"	4.1	71.1	100.0	63.4	10.8	36.6
3/8"	3.2	44.2	100.0	54.4	9.0	45.6
#4	2.4	7.7	97.4	41.3	13.1	58.7
#8	2.2	3.3	85.3	35.0	6.2	65.0
#16	2.0	2.4	71.7	29.4	5.7	70.6
#30	1.9	2.2	52.1	21.6	7.8	78.4
#50	1.8	1.9	22.9	10.1	11.5	89.9
#100	1.7	1.8	2.5	2.0	8.0	98.0
LBW	1.4	1.4	0.5	1.0	1.0	99.0

\*Maximum % Retained must be above the 3/8" sieve.  
 \*Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.  
 \*% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.  
 \*% Retained must be at least 8% for the 1" sieve when a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation  Batch Plant Gradations  Aggregate Supplier Gradations

<b>Coarseness Factor:</b>	<b>70</b>	<b>Workability Factor:</b>	<b>35</b>
---------------------------	-----------	----------------------------	-----------



Initial Production Sample (IPS)

Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	85.0	15.0	15.0
3/4"	72.1	12.9	27.9
1/2"	64.5	7.6	35.5
3/8"	56.5	8.0	43.5
#4	42.7	13.8	57.3
#8	34.9	7.8	65.1
#16	29.0	5.9	71.0
#30	21.0	8.0	79.0
#50	8.2	12.8	91.8
#100	1.6	6.5	98.4
LBW	0.7	0.9	99.3

PREPARED BY:  
 SM, LLC Technical Service

Approved By:

# Aggregate Optimization Chart

**PLANT #:** **P-39**

Sample Date: 6/8/20

Concrete Grade: **P1M**

Contractor: \_\_\_\_\_

Dates Test Represents: 6/9/2020 through 6/15/2020

MDOT No.: \_\_\_\_\_

Agg. Class	Pit #	Source	Weight (SSD)	ft <sup>3</sup>	Specific Gravity	% Contribution
CA	71-47	Presque Isle	1000	6.12	2.62	32.6
IA	71-47	Presque Isle	850	5.20	2.62	27.7
2NS	44-051	Krake Willis Rd	1220	7.38	2.65	39.7
<b>Total Wt</b>			<b>3070</b>	<b>18.69</b>		<b>100.0</b>

<----- Verify this number is 100%




**Superior Materials, LLC**  
 30701 W. 10 Mile Rd.  
 Suite 500  
 Farmington Hills, MI 48336

Sieve	CA	IA	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	47.4	100.0	100.0	82.9	17.1	17.1
3/4"	14.9	98.3	100.0	71.8	11.1	28.2
1/2"	3.0	79.0	100.0	62.6	9.2	37.4
3/8"	2.3	54.1	100.0	55.5	7.1	44.5
#4	1.8	10.0	95.2	41.2	14.3	58.8
#8	1.7	4.1	80.1	33.5	7.7	66.5
#16	1.6	2.8	64.3	26.8	6.7	73.2
#30	1.6	2.4	48.3	20.4	6.5	79.6
#50	1.6	2.2	22.8	10.2	10.2	89.8
#100	1.5	2.1	6.1	3.5	6.7	96.5
LBW	1.3	1.9	0.7	1.2	2.3	98.8

\*Maximum % Retained must be above the 3/8" sieve.  
 \*Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.  
 \*% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.  
 \*% Retained must be at least 8% for the 1" sieve when a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation  Batch Plant Gradations  Aggregate Supplier Gradations

**Coarseness Factor:** **67**      **Workability Factor:** **34**



Initial Production Sample (IPS)

**Coarseness Factor:** **65**  
**Workability Factor:** **35**

Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	99.6	0.4	0.4
1"	83.9	15.7	16.1
3/4"	74.1	9.8	25.9
1/2"	64.3	9.7	35.7
3/8"	57.5	6.8	42.5
#4	44.5	13.1	55.5
#8	35.1	9.4	64.9
#16	27.9	7.2	72.1
#30	21.7	6.2	78.3
#50	12.6	9.1	87.4
#100	3.5	9.1	96.5
LBW	1.2	2.4	98.8

PREPARED BY:  
 SM, LLC Technical Service

Approved By:

# Aggregate Optimization Chart

**PLANT #:** **P-02**

Sample Date: 6/8/20 Concrete Grade: **P1M**  
 Dates Test Represents: 6/9/2020 through 6/15/2020

Contractor: \_\_\_\_\_

MDOT No.: \_\_\_\_\_

Agg. Class	Pit #	Source	Weight (SSD)	ft <sup>3</sup>	Specific Gravity	% Contribution
CA	71-47	Presque Isle	900	5.50	2.62	29.3
IA	71-47	Presque Isle	920	5.63	2.62	30.0
2NS	63-115	Ray Rd	1250	7.56	2.65	40.7
<b>Total Wt</b>			<b>3070</b>	<b>18.69</b>		<b>100.0</b>

<----- Verify this number is 100%




**Superior Materials, LLC**  
 30701 W. 10 Mile Rd.  
 Suite 500  
 Farmington Hills, MI 48336

Sieve	CA	IA	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	96.1	100.0	100.0	98.9	1.1	1.1
1"	42.9	100.0	100.0	83.3	15.6	16.7
3/4"	11.6	97.8	100.0	73.4	9.8	26.6
1/2"	4.1	71.1	100.0	63.2	10.2	36.8
3/8"	3.2	44.2	100.0	54.9	8.3	45.1
#4	2.4	7.7	98.4	43.1	11.8	56.9
#8	2.2	3.3	79.8	34.1	9.0	65.9
#16	2.0	2.4	61.9	26.5	7.6	73.5
#30	1.9	2.2	46.2	20.0	6.5	80.0
#50	1.8	1.9	24.7	11.2	8.9	88.8
#100	1.7	1.8	5.3	3.2	8.0	96.8
LBW	1.4	1.4	0.5	1.0	2.2	99.0

\*Maximum % Retained must be above the 3/8" sieve.  
 \*Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.  
 \*% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.  
 \*% Retained must be at least 8% for the 1" sieve when a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation  Batch Plant Gradations  Aggregate Supplier Gradations

**Coarseness Factor:** **68** **Workability Factor:** **34**



Initial Production Sample (IPS)

**Coarseness Factor:** **67**  
**Workability Factor:** **35**

Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	85.0	15.0	15.0
3/4"	72.3	12.7	27.7
1/2"	64.5	7.8	35.5
3/8"	56.5	8.0	43.5
#4	42.7	13.8	57.3
#8	34.9	7.8	65.1
#16	29.0	5.9	71.0
#30	21.0	8.0	79.0
#50	8.2	12.8	91.8
#100	1.6	6.5	98.4
LBW	0.7	0.9	99.3

PREPARED BY:  
 SM, LLC Technical Service

Approved By: