

Aggregate Optimization Chart

PLANT #: **P-102**

Sample Date: 9/2/24

Concrete Grade: **P1M, 3500HP**

Contractor: _____

Dates Test Represents: 9/3/2024 through 9/9/2024

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
CA	58-003	Stoneco	1470	8.76	2.69	47.1
IA	58-003	Stoneco	450	2.68	2.69	14.4
2NS	63-114	Highland	1200	7.26	2.65	38.5
Total Wt			3120	18.70		100.0

<----- Verify this number is 100%




Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Sieve	CA	IA	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	56.8	100.0	100.0	79.6	20.4	20.4
3/4"	32.4	100.0	100.0	68.2	11.5	31.9
1/2"	16.1	92.9	100.0	59.4	8.7	40.6
3/8"	10.0	72.1	100.0	53.6	5.9	46.4
#4	2.8	17.2	99.0	41.9	11.7	58.1
#8	1.8	3.4	85.9	34.4	7.5	65.6
#16	1.5	1.8	69.7	27.8	6.6	72.2
#30	1.3	1.4	51.8	20.7	7.0	79.3
#50	1.2	1.2	23.7	9.9	10.9	90.1
#100	1.1	1.2	4.7	2.5	7.4	97.5
LBW	0.6	1.0	1.1	0.9	1.6	99.2

*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 8% for the 1" sieve when a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Coarseness Factor: **71** **Workability Factor:** **34**



Initial Production Sample (IPS)

Coarseness Factor: **67**
Workability Factor: **35**

Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	85.5	14.5	14.5
3/4"	73.4	12.1	26.6
1/2"	61.0	12.4	39.0
3/8"	56.2	4.8	43.8
#4	43.1	13.1	56.9
#8	34.9	8.2	65.1
#16	29.4	5.5	70.6
#30	21.6	7.8	78.4
#50	8.1	13.4	91.9
#100	2.2	5.9	97.8
LBW	1.4	0.8	98.6

PREPARED BY:
 SM, LLC Technical Service

Approved By:

Aggregate Optimization Chart

PLANT #: **P-103**

Sample Date: 9/2/24

Concrete Grade: **P1M, 3500HP**

Dates Test Represents: 9/3/2024 through 9/9/2024

Contractor: _____

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
CA	58-003	Stoneco	1470	8.76	2.69	47.1
IA	58-003	Stoneco	450	2.68	2.69	14.4
2NS	63-114	Highland	1200	7.26	2.65	38.5
Total Wt			3120	18.70		100.0

<----- Verify this number is 100%




Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Sieve	CA	IA	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	56.8	100.0	100.0	79.6	20.4	20.4
3/4"	32.4	100.0	100.0	68.2	11.5	31.9
1/2"	16.1	92.9	100.0	59.4	8.7	40.6
3/8"	10.0	72.1	100.0	53.6	5.9	46.4
#4	2.8	17.2	99.0	41.9	11.7	58.1
#8	1.8	3.4	85.9	34.4	7.5	65.6
#16	1.5	1.8	69.7	27.8	6.6	72.2
#30	1.3	1.4	51.8	20.7	7.0	79.3
#50	1.2	1.2	23.7	9.9	10.9	90.1
#100	1.1	1.2	4.7	2.5	7.4	97.5
LBW	0.6	1.0	1.1	0.9	1.6	99.2

*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 8% for the 1" sieve when a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Coarseness Factor: **71** **Workability Factor:** **34**



Initial Production Sample (IPS)

Coarseness Factor: **67**
Workability Factor: **35**

Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	85.5	14.5	14.5
3/4"	73.4	12.1	26.6
1/2"	61.0	12.4	39.0
3/8"	56.2	4.8	43.8
#4	43.1	13.1	56.9
#8	34.9	8.2	65.1
#16	29.4	5.5	70.6
#30	21.6	7.8	78.4
#50	8.1	13.4	91.9
#100	2.2	5.9	97.8
LBW	1.4	0.8	98.6

PREPARED BY:
 SM, LLC Technical Service

Approved BY:

Aggregate Optimization Chart

PLANT #: 15

Sample Date: 9/2/24

Concrete Grade: **P1M, 3500HP**

Dates Test Represents: 9/3/2024 through 9/9/2024

Contractor: _____

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
CA	58-003	Stoneco	1470	8.76	2.69	47.1
IA	58-003	Stoneco	450	2.68	2.69	14.4
2NS	81-019	Pleasant Lake	1200	7.26	2.65	38.5
Total Wt			3120	18.70		100.0

<----- Verify this number is 100%




Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Sieve	CA	IA	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	56.8	100.0	100.0	79.6	20.4	20.4
3/4"	32.4	100.0	100.0	68.2	11.5	31.9
1/2"	16.1	92.9	100.0	59.4	8.7	40.6
3/8"	10.0	72.1	100.0	53.6	5.9	46.4
#4	2.8	17.2	97.3	41.2	12.3	58.8
#8	1.8	3.4	83.4	33.4	7.8	66.6
#16	1.5	1.8	63.7	25.5	7.9	74.5
#30	1.3	1.4	42.9	17.3	8.2	82.7
#50	1.2	1.2	21.7	9.1	8.2	90.9
#100	1.1	1.2	4.8	2.5	6.5	97.5
LBW	0.6	1.0	0.6	0.7	1.9	99.3

*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 8% for the 1" sieve when a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Coarseness Factor:	70	Workability Factor:	33
---------------------------	-----------	----------------------------	-----------



Initial Production Sample (IPS)

Coarseness Factor:	67		
Workability Factor:	35		
Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	85.5	14.5	14.5
3/4"	73.4	12.1	26.6
1/2"	61.0	12.4	39.0
3/8"	56.2	4.8	43.8
#4	43.1	13.1	56.9
#8	34.9	8.2	65.1
#16	29.4	5.5	70.6
#30	21.6	7.8	78.4
#50	8.1	13.4	91.9
#100	2.2	5.9	97.8
LBW	1.4	0.8	98.6

PREPARED BY:
 SM, LLC Technical Service

Approved By:

Aggregate Optimization Chart

PLANT #: 12

Sample Date: 9/2/24

Concrete Grade: **P1M, 3500HP**

Dates Test Represents: 9/3/2024 through 9/9/2024

Contractor: _____

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
CA	71-47	Presque Isle	1020	6.24	2.62	33.2
IA	71-47	Presque Isle	850	5.20	2.62	27.7
2NS	63-115	Ray Rd	1200	7.26	2.65	39.1
Total Wt			3070	18.70		100.0

<----- Verify this number is 100%




Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Sieve	CA	IA	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	27.6	100.0	100.0	75.9	24.1	24.1
3/4"	4.2	99.0	100.0	67.9	8.1	32.1
1/2"	1.1	72.4	100.0	59.5	8.4	40.5
3/8"	1.1	46.0	100.0	52.2	7.3	47.8
#4	1.1	9.2	96.9	40.8	11.4	59.2
#8	1.1	3.0	79.3	32.2	8.6	67.8
#16	1.1	2.2	62.9	25.6	6.6	74.4
#30	1.0	2.1	47.5	19.5	6.1	80.5
#50	1.0	2.0	26.3	11.2	8.3	88.8
#100	0.9	2.0	6.9	3.5	7.6	96.5
LBW	0.8	1.7	0.8	1.0	2.5	99.0

*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 8% for the 1" sieve when a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Coarseness Factor: 71 **Workability Factor:** 32



Initial Production Sample (IPS)

Coarseness Factor: 67
Workability Factor: 35

Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	99.6	0.4	0.4
1"	83.9	15.7	16.1
3/4"	74.0	9.8	26.0
1/2"	63.7	10.3	36.3
3/8"	56.4	7.3	43.6
#4	43.0	13.4	57.0
#8	35.1	7.9	64.9
#16	29.0	6.1	71.0
#30	20.9	8.0	79.1
#50	8.1	12.8	91.9
#100	1.6	6.5	98.4
LBW	0.9	0.8	99.1

PREPARED BY:
 SM, LLC Technical Service

Approved By:

Aggregate Optimization Chart

PLANT #: 21

Sample Date: 9/2/24

Concrete Grade: **P1M, 3500HP**

Dates Test Represents: 9/3/2024 through 9/9/2024

Contractor: _____

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
CA	58-003	Stoneco	1470	8.76	2.69	47.1
IA	58-003	Stoneco	450	2.68	2.69	14.4
2NS	81-019	Pleasant Lake	1200	7.26	2.65	38.5
Total Wt			3120	18.70		100.0

<----- Verify this number is 100%




Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Sieve	CA	IA	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	56.8	100.0	100.0	79.6	20.4	20.4
3/4"	32.4	100.0	100.0	68.2	11.5	31.9
1/2"	16.1	92.9	100.0	59.4	8.7	40.6
3/8"	10.0	72.1	100.0	53.6	5.9	46.4
#4	2.8	17.2	97.3	41.2	12.3	58.8
#8	1.8	3.4	83.4	33.4	7.8	66.6
#16	1.5	1.8	63.7	25.5	7.9	74.5
#30	1.3	1.4	42.9	17.3	8.2	82.7
#50	1.2	1.2	21.7	9.1	8.2	90.9
#100	1.1	1.2	4.8	2.5	6.5	97.5
LBW	0.6	1.0	0.6	0.7	1.9	99.3

*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 8% for the 1" sieve when a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Coarseness Factor: 70 **Workability Factor:** 33



Initial Production Sample (IPS)

Coarseness Factor: 67
Workability Factor: 35

Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	86.9	13.1	13.1
3/4"	76.1	10.8	23.9
1/2"	63.7	12.4	36.3
3/8"	56.2	7.5	43.8
#4	43.2	13.0	56.8
#8	34.7	8.5	65.3
#16	27.5	7.2	72.5
#30	20.6	7.0	79.4
#50	9.0	11.6	91.0
#100	2.1	6.9	97.9
LBW	1.0	1.1	99.0

PREPARED BY:
 SM, LLC Technical Service

Approved By:

Aggregate Optimization Chart

PLANT #: P11

Sample Date: 9/2/24

Concrete Grade: P1M, 3500HP

Contractor: _____

Dates Test Represents: 9/3/2024 through 9/9/2024

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
CA	71-47	Presque Isle	950	5.81	2.62	30.9
IA	71-47	Presque Isle	920	5.63	2.62	30.0
2NS	63-115	Ray Rd	1200	7.26	2.65	39.1
Total Wt			3070	18.70		100.0

<----- Verify this number is 100%




Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Sieve	CA	IA	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	27.6	100.0	100.0	77.6	22.4	22.4
3/4"	4.2	99.0	100.0	70.1	7.5	29.9
1/2"	1.1	72.4	100.0	61.1	8.9	38.9
3/8"	1.1	46.0	100.0	53.2	7.9	46.8
#4	1.1	9.2	96.9	41.0	12.2	59.0
#8	1.1	3.0	79.3	32.2	8.7	67.8
#16	1.1	2.2	62.9	25.6	6.7	74.4
#30	1.0	2.1	47.5	19.5	6.1	80.5
#50	1.0	2.0	26.3	11.2	8.3	88.8
#100	0.9	2.0	6.9	3.6	7.6	96.4
LBW	0.8	1.7	0.8	1.1	2.5	98.9

*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 8% for the 1" sieve when a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Coarseness Factor: 69 **Workability Factor:** 32



Initial Production Sample (IPS)

Coarseness Factor: 65
Workability Factor: 36

Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	99.0	0.6	0.6
1"	84.0	15.3	16.0
3/4"	73.5	10.5	26.5
1/2"	65.2	8.2	34.8
3/8"	58.2	7.1	41.8
#4	44.1	14.1	55.9
#8	35.5	8.6	64.5
#16	29.1	6.4	70.9
#30	21.9	7.3	78.1
#50	9.6	12.2	90.4
#100	2.6	7.1	97.4
LBW	1.0	1.6	99.0

PREPARED BY:
 SM, LLC Technical Service

Approved By:

Aggregate Optimization Chart

PLANT #: **P-35**

Sample Date: 9/2/24

Concrete Grade: **P1M, 3500HP**

Dates Test Represents: 9/3/2024 through 9/9/2024

Contractor: _____

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
CA	58-003	Stoneco	1470	8.76	2.69	47.1
IA	58-003	Stoneco	450	2.68	2.69	14.4
2NS	81-019	Pleasant Lake	1200	7.26	2.65	38.5
Total Wt			3120	18.70		100.0

<----- Verify this number is 100%




Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Sieve	CA	IA	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	56.8	100.0	100.0	79.6	20.4	20.4
3/4"	32.4	100.0	100.0	68.2	11.5	31.9
1/2"	16.1	92.9	100.0	59.4	8.7	40.6
3/8"	10.0	72.1	100.0	53.6	5.9	46.4
#4	2.8	17.2	97.3	41.2	12.3	58.8
#8	1.8	3.4	83.4	33.4	7.8	66.6
#16	1.5	1.8	63.7	25.5	7.9	74.5
#30	1.3	1.4	42.9	17.3	8.2	82.7
#50	1.2	1.2	21.7	9.1	8.2	90.9
#100	1.1	1.2	4.8	2.5	6.5	97.5
LBW	0.6	1.0	0.6	0.7	1.9	99.3

*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 8% for the 1" sieve when a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Coarseness Factor: **70** **Workability Factor:** **33**



Initial Production Sample (IPS)

Coarseness Factor: **67**
Workability Factor: **35**

Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	86.9	13.1	13.1
3/4"	76.1	10.8	23.9
1/2"	63.7	12.4	36.3
3/8"	56.2	7.5	43.8
#4	43.2	13.0	56.8
#8	34.7	8.5	65.3
#16	27.5	7.2	72.5
#30	20.6	7.0	79.4
#50	9.0	11.6	91.0
#100	2.1	6.9	97.9
LBW	1.0	1.1	99.0

PREPARED BY:
 SM, LLC Technical Service

Approved By:

Aggregate Optimization Chart

PLANT #: **P-36**

Sample Date: 9/2/24

Concrete Grade: **P1M, 3500HP**

Contractor: _____

Dates Test Represents: 9/3/2024 through 9/9/2024

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
CA	71-47	Presque Isle	970	5.93	2.62	31.6
IA	71-47	Presque Isle	900	5.50	2.62	29.3
2NS	63-92	Grange Hall	1200	7.26	2.65	39.1
Total Wt			3070	18.70		100.0

<----- Verify this number is 100%




Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Sieve	CA	IA	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	27.6	100.0	100.0	77.1	22.9	22.9
3/4"	4.2	99.0	100.0	69.4	7.7	30.6
1/2"	1.1	72.4	100.0	60.7	8.8	39.3
3/8"	1.1	46.0	100.0	52.9	7.7	47.1
#4	1.1	9.2	98.0	41.4	11.6	58.6
#8	1.1	3.0	83.8	34.0	7.4	66.0
#16	1.1	2.2	69.1	28.0	6.0	72.0
#30	1.0	2.1	51.4	21.0	7.0	79.0
#50	1.0	2.0	23.5	10.1	10.9	89.9
#100	0.9	2.0	3.4	2.2	7.9	97.8
LBW	0.8	1.7	0.6	1.0	1.2	99.0

*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 8% for the 1" sieve when a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Coarseness Factor: **71** **Workability Factor:** **34**



Initial Production Sample (IPS)

Coarseness Factor: **67**
Workability Factor: **35**

Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	85.0	15.0	15.0
3/4"	72.1	12.9	27.9
1/2"	64.5	7.6	35.5
3/8"	56.5	8.0	43.5
#4	42.7	13.8	57.3
#8	34.9	7.8	65.1
#16	29.0	5.9	71.0
#30	21.0	8.0	79.0
#50	8.2	12.8	91.8
#100	1.6	6.5	98.4
LBW	0.7	0.9	99.3

PREPARED BY:
 SM, LLC Technical Service

Approved By:

Aggregate Optimization Chart

PLANT #: **P-39**

Sample Date: 9/2/24

Concrete Grade: **P1M, 3500HP**

Dates Test Represents: 9/3/2024 through 9/9/2024

Contractor: _____

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
CA	71-47	Presque Isle	920	5.63	2.62	30.0
IA	71-47	Presque Isle	900	5.50	2.62	29.3
2NS	44-051	Krake Willis Rd	1250	7.56	2.65	40.7
Total Wt			3070	18.69		100.0

<----- Verify this number is 100%




Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Sieve	CA	IA	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	27.6	100.0	100.0	78.3	21.7	21.7
3/4"	4.2	99.0	100.0	71.0	7.3	29.0
1/2"	1.1	72.4	100.0	62.3	8.7	37.7
3/8"	1.1	46.0	100.0	54.5	7.7	45.5
#4	1.1	9.2	99.2	43.4	11.1	56.6
#8	1.1	3.0	83.6	35.2	8.2	64.8
#16	1.1	2.2	67.8	28.6	6.7	71.4
#30	1.0	2.1	49.6	21.1	7.5	78.9
#50	1.0	2.0	21.4	9.6	11.5	90.4
#100	0.9	2.0	5.1	2.9	6.7	97.1
LBW	0.8	1.7	0.4	0.9	2.0	99.1

*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 8% for the 1" sieve when a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Coarseness Factor: **70** Workability Factor: **35**



Initial Production Sample (IPS)

Coarseness Factor: **65**
 Workability Factor: **35**

Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	99.6	0.4	0.4
1"	83.9	15.7	16.1
3/4"	74.1	9.8	25.9
1/2"	64.3	9.7	35.7
3/8"	57.5	6.8	42.5
#4	44.5	13.1	55.5
#8	35.1	9.4	64.9
#16	27.9	7.2	72.1
#30	21.7	6.2	78.3
#50	12.6	9.1	87.4
#100	3.5	9.1	96.5
LBW	1.2	2.4	98.8

PREPARED BY:
 SM, LLC Technical Service

Approved By:

Aggregate Optimization Chart

PLANT #: **P-02**

Sample Date: 9/2/24

Concrete Grade: **P1M, 3500HP**

Contractor: _____

Dates Test Represents: 9/3/2024 through 9/9/2024

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
CA	71-47	Presque Isle	1020	6.24	2.62	33.2
IA	71-47	Presque Isle	850	5.20	2.62	27.7
2NS	63-115	Ray Rd	1200	7.26	2.65	39.1
Total Wt			3070	18.70		100.0

<----- Verify this number is 100%




Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Sieve	CA	IA	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	27.6	100.0	100.0	75.9	24.1	24.1
3/4"	4.2	99.0	100.0	67.9	8.1	32.1
1/2"	1.1	72.4	100.0	59.5	8.4	40.5
3/8"	1.1	46.0	100.0	52.2	7.3	47.8
#4	1.1	9.2	96.9	40.8	11.4	59.2
#8	1.1	3.0	79.3	32.2	8.6	67.8
#16	1.1	2.2	62.9	25.6	6.6	74.4
#30	1.0	2.1	47.5	19.5	6.1	80.5
#50	1.0	2.0	26.3	11.2	8.3	88.8
#100	0.9	2.0	6.9	3.5	7.6	96.5
LBW	0.8	1.7	0.8	1.0	2.5	99.0

*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 8% for the 1" sieve when a 2" max. size (nom. Max. 1.5") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Coarseness Factor:	71	Workability Factor:	32
---------------------------	-----------	----------------------------	-----------



Initial Production Sample (IPS)

Coarseness Factor:	67		
Workability Factor:	35		
Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	85.0	15.0	15.0
3/4"	72.3	12.7	27.7
1/2"	64.5	7.8	35.5
3/8"	56.5	8.0	43.5
#4	42.7	13.8	57.3
#8	34.9	7.8	65.1
#16	29.0	5.9	71.0
#30	21.0	8.0	79.0
#50	8.2	12.8	91.8
#100	1.6	6.5	98.4
LBW	0.7	0.9	99.3

PREPARED BY:
 SM, LLC Technical Service

Approved By: