

Aggregate Optimization Chart

Production Gradation Report

PLANT #: **P-102**

Sample Date: 10/28/24

Concrete Grade: DM, 4500HP

Contractor: _____

Dates Test Represents: 10/29/2024 through 11/4/2024

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
6AA	58-003	Stoneco	1450	8.64	2.69	49.2
26A	58-003	Stoneco	350	2.09	2.69	11.9
2NS	63-114	Highland	1150	6.95	2.65	39.0
Total Wt			2950	17.68		100.0

<----- Verify this number is 100%



Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Sieve	6AA	26A	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	100.0	100.0	100.0	100.0	0.0	0.0
3/4"	85.0	100.0	100.0	92.6	7.4	7.4
1/2"	38.7	99.7	100.0	69.8	22.8	30.2
3/8"	15.0	89.5	100.0	57.0	12.9	43.0
#4	2.3	7.0	99.1	40.6	16.4	59.4
#8	1.4	1.9	84.5	33.9	6.7	66.1
#16	0.8	1.6	65.4	26.1	7.8	73.9
#30	0.7	1.5	43.8	17.6	8.5	82.4
#50	0.7	1.4	18.0	7.5	10.1	92.5
#100	0.6	1.3	3.8	1.9	5.6	98.1
LBW	0.9	1.2	0.6	0.8	1.1	99.2

*Maximum % Retained must be above the 3/8" sieve.

*Any two adjacent sieves must equal 10% except max.,

nom. max., #100 and #200 sieves.

*% Retained must be at least 4% for each sieve except max.,

nom. max., #100 and #200 sieves.

*% Retained must be at least 4% for the 3/4" sieve when

a 1.5" max. size (nom. Max. 1.0") aggregate is used.


Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Adjusted WF Initial Production Sample (IPS)

Coarseness Factor:	65	Workability Factor:	34	36.4
---------------------------	-----------	----------------------------	-----------	-------------

Coarseness Factor:	61
---------------------------	-----------

Workability Factor:	36
----------------------------	-----------



Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	99.3	0.7	0.7
3/4"	89.2	10.1	10.8
1/2"	70.7	18.5	29.3
3/8"	60.7	10.0	39.3
#4	44.4	16.3	55.6
#8	35.9	8.5	64.1
#16	27.3	8.6	72.7
#30	19.1	8.2	80.9
#50	7.4	11.7	92.6
#100	1.9	5.6	98.1
LBW	0.7	1.2	99.3

PREPARED BY:
 SM, LLC Technical Service

Approved By:

Aggregate Optimization Chart

Production Gradation Report

PLANT #: P-103

Sample Date: 10/28/24

Concrete Grade: **DM, 4500HP**

Contractor: _____

Dates Test Represents: 10/29/2024 through 11/4/2024

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
6AA	58-003	Stoneco	1450	8.64	2.69	49.2
26A	58-003	Stoneco	350	2.09	2.69	11.9
2NS	63-114	Highland	1150	6.95	2.65	39.0
Total Wt			2950	17.68		100.0

<----- Verify this number is 100%



Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Sieve	6AA	26A	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	100.0	100.0	100.0	100.0	0.0	0.0
3/4"	85.0	100.0	100.0	92.6	7.4	7.4
1/2"	38.7	99.7	100.0	69.8	22.8	30.2
3/8"	15.0	89.5	100.0	57.0	12.9	43.0
#4	2.3	7.0	99.1	40.6	16.4	59.4
#8	1.4	1.9	84.5	33.9	6.7	66.1
#16	0.8	1.6	65.4	26.1	7.8	73.9
#30	0.7	1.5	43.8	17.6	8.5	82.4
#50	0.7	1.4	18.0	7.5	10.1	92.5
#100	0.6	1.3	3.8	1.9	5.6	98.1
LBW	0.9	1.2	0.6	0.8	1.1	99.2


*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for the 3/4" sieve when a 1.5" max. size (nom. Max. 1.0") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations Adjusted WF Initial Production Sample (IPS)

Coarseness Factor: 65	Workability Factor: 34	Adjusted WF: 36.4
------------------------------	-------------------------------	--------------------------

Coarseness Factor: 61

Workability Factor: 36



Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	99.3	0.7	0.7
3/4"	89.2	10.1	10.8
1/2"	70.7	18.5	29.3
3/8"	60.7	10.0	39.3
#4	44.4	16.3	55.6
#8	35.9	8.5	64.1
#16	27.3	8.6	72.7
#30	19.1	8.2	80.9
#50	7.4	11.7	92.6
#100	1.9	5.6	98.1
LBW	0.7	1.2	99.3

PREPARED BY:
 SM, LLC Technical Service

Approved BY:

Aggregate Optimization Chart

PLANT #: 12

Sample Date: 10/28/24

Dates Test Represents: 10/29/2024 through 11/4/2024

Concrete Grade: DM, 4500HP

Contractor: _____

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
6AA	71-47	Presque Isle	1500	9.17	2.62	51.6
26A	71-47	Presque Isle	255	1.56	2.62	8.8
2NS	63-115	Ray Rd	1150	6.95	2.65	39.6
Total Wt			2905	17.69		100.0

<----- Verify this number is 100%



Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336


Sieve	6AA	26A	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	100.0	100.0	100.0	100.0	0.0	0.0
3/4"	81.0	100.0	100.0	90.2	9.8	9.8
1/2"	44.8	95.3	100.0	71.1	19.1	28.9
3/8"	26.9	83.7	100.0	60.8	10.3	39.2
#4	4.8	18.6	96.9	42.5	18.4	57.5
#8	2.1	4.5	80.2	33.2	9.2	66.8
#16	1.8	2.5	64.1	26.5	6.7	73.5
#30	1.6	2.1	49.1	20.4	6.1	79.6
#50	1.6	1.9	26.1	11.3	9.1	88.7
#100	1.5	1.8	6.6	3.5	7.8	96.5
LBW	1.3	1.7	1.0	1.2	2.3	98.8

*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for the 3/4" sieve when a 1.5" max. size (nom. Max. 1.0") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Adjusted WF Initial Production Sample (IPS)

Coarseness Factor:	59	Workability Factor:	33	Adjusted WF	35.7	Coarseness Factor:	63
---------------------------	-----------	----------------------------	-----------	--------------------	-------------	---------------------------	-----------



Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	99.3	0.7	0.7
3/4"	89.0	10.3	11.0
1/2"	70.3	18.7	29.7
3/8"	59.9	10.4	40.1
#4	41.9	18.0	58.1
#8	35.9	6.0	64.1
#16	27.8	8.2	72.2
#30	18.9	8.8	81.1
#50	6.3	12.6	93.7
#100	1.7	4.6	98.3
LBW	1.0	0.7	99.0

PREPARED BY:
 SM, LLC Technical Service

Approved By:

Aggregate Optimization Chart

PLANT #: p11

Sample Date: 10/28/24

Concrete Grade: DM, 4500HP

Contractor: _____

Dates Test Represents: 10/29/2024 through 11/4/2024

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
6AA	71-47	Presque Isle	1500	9.17	2.62	51.6
26A	71-47	Presque Isle	255	1.56	2.62	8.8
2NS	63-115	Ray Rd	1150	6.95	2.65	39.6
Total Wt			2905	17.69		100.0

<----- Verify this number is 100%



Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336


Sieve	6AA	26A	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	100.0	100.0	100.0	100.0	0.0	0.0
3/4"	81.0	100.0	100.0	90.2	9.8	9.8
1/2"	44.8	95.3	100.0	71.1	19.1	28.9
3/8"	26.9	83.7	100.0	60.8	10.3	39.2
#4	4.8	18.6	96.9	42.5	18.4	57.5
#8	2.1	4.5	80.2	33.2	9.2	66.8
#16	1.8	2.5	64.1	26.5	6.7	73.5
#30	1.6	2.1	49.1	20.4	6.1	79.6
#50	1.6	1.9	26.1	11.3	9.1	88.7
#100	1.5	1.8	6.6	3.5	7.8	96.5
LBW	1.3	1.7	1.0	1.2	2.3	98.8

*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for the 3/4" sieve when a 1.5" max. size (nom. Max. 1.0") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Adjusted WF Initial Production Sample (IPS)

Coarseness Factor:	59	Workability Factor:	33	Adjusted WF	35.7	Coarseness Factor:	62
---------------------------	-----------	----------------------------	-----------	--------------------	-------------	---------------------------	-----------



Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	100.0	0.0	0.0
3/4"	95.0	5.0	5.0
1/2"	72.3	22.8	27.7
3/8"	60.4	11.8	39.6
#4	42.6	17.8	57.4
#8	36.0	6.6	64.0
#16	29.5	6.5	70.5
#30	20.3	9.2	79.7
#50	9.5	10.8	90.5
#100	3.4	6.1	96.6
LBW	1.3	2.1	98.7

PREPARED BY:
 SM, LLC Technical Service

Approved By:

Aggregate Optimization Chart

Production Gradation Report

PLANT #: **P-02**

Sample Date: 10/28/24

Concrete Grade: DM, 4500HP

Contractor: _____

Dates Test Represents: 10/29/2024 through 11/4/2024

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
6AA	71-47	Presque Isle	1500	9.17	2.62	51.6
26A	71-47	Presque Isle	255	1.56	2.62	8.8
2NS	63-115	Ray Rd	1150	6.95	2.65	39.6
Total Wt			2905	17.69		100.0

<----- Verify this number is 100%




Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Sieve	6AA	26A	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	100.0	100.0	100.0	100.0	0.0	0.0
3/4"	81.0	100.0	100.0	90.2	9.8	9.8
1/2"	44.8	95.3	100.0	71.1	19.1	28.9
3/8"	26.9	83.7	100.0	60.8	10.3	39.2
#4	4.8	18.6	96.9	42.5	18.4	57.5
#8	2.1	4.5	80.2	33.2	9.2	66.8
#16	1.8	2.5	64.1	26.5	6.7	73.5
#30	1.6	2.1	49.1	20.4	6.1	79.6
#50	1.6	1.9	26.1	11.3	9.1	88.7
#100	1.5	1.8	6.6	3.5	7.8	96.5
LBW	1.3	1.7	1.0	1.2	2.3	98.8

*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for the 3/4" sieve when a 1.5" max. size (nom. Max. 1.0") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations Adjusted WF Initial Production Sample (IPS)

Coarseness Factor: 59	Workability Factor: 33	35.7	Coarseness Factor: 63
-------------------------------------	--------------------------------------	-------------	-------------------------------------



Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	100.0	0.0	0.0
3/4"	95.1	4.9	4.9
1/2"	74.6	20.5	25.4
3/8"	59.3	15.3	40.7
#4	42.1	17.2	57.9
#8	35.1	7.1	64.9
#16	29.2	5.9	70.8
#30	21.9	7.3	78.1
#50	9.6	12.4	90.4
#100	2.4	7.2	97.6
LBW	0.9	1.5	99.1

PREPARED BY:
 SM, LLC Technical Service

Approved By: