

Aggregate Optimization Chart

Production Gradation Report

PLANT #: **P-102**

Sample Date: 11/11/24

Concrete Grade: DM, 4500HP

Contractor: _____

Dates Test Represents: 11/12/2024 through 11/18/2024

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
6AA	58-003	Stoneco	1500	8.94	2.69	50.8
26A	58-003	Stoneco	300	1.79	2.69	10.2
2NS	63-114	Highland	1150	6.95	2.65	39.0
Total Wt			2950	17.68		100.0

<----- Verify this number is 100%



Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Sieve	6AA	26A	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	99.7	100.0	100.0	99.8	0.2	0.2
3/4"	81.1	100.0	100.0	90.4	9.5	9.6
1/2"	43.9	99.3	100.0	71.4	19.0	28.6
3/8"	22.6	88.2	100.0	59.4	12.0	40.6
#4	3.3	11.5	98.9	41.4	18.0	58.6
#8	2.0	2.4	85.0	34.4	7.0	65.6
#16	1.0	1.3	66.3	26.5	7.9	73.5
#30	0.9	1.1	45.4	18.3	8.2	81.7
#50	0.8	1.0	21.0	8.7	9.6	91.3
#100	0.8	1.0	4.5	2.3	6.4	97.7
LBW	0.7	0.9	0.3	0.6	1.7	99.4

*Maximum % Retained must be above the 3/8" sieve.

*Any two adjacent sieves must equal 10% except max.,

nom. max., #100 and #200 sieves.

*% Retained must be at least 4% for each sieve except max.,

nom. max., #100 and #200 sieves.

*% Retained must be at least 4% for the 3/4" sieve when

a 1.5" max. size (nom. Max. 1.0") aggregate is used.


Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Adjusted WF Initial Production Sample (IPS)

Coarseness Factor:	62	Workability Factor:	34	36.9
---------------------------	-----------	----------------------------	-----------	-------------

Coarseness Factor:	61
---------------------------	-----------

Workability Factor:	36
----------------------------	-----------



Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	99.3	0.7	0.7
3/4"	89.2	10.1	10.8
1/2"	70.7	18.5	29.3
3/8"	60.7	10.0	39.3
#4	44.4	16.3	55.6
#8	35.9	8.5	64.1
#16	27.3	8.6	72.7
#30	19.1	8.2	80.9
#50	7.4	11.7	92.6
#100	1.9	5.6	98.1
LBW	0.7	1.2	99.3

PREPARED BY:
 SM, LLC Technical Service

Approved By:

Aggregate Optimization Chart

Production Gradation Report

PLANT #: **P-103**

Sample Date: 11/11/24

Concrete Grade: **DM, 4500HP**

Contractor: _____

Dates Test Represents: 11/12/2024 through 11/18/2024

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
6AA	58-003	Stoneco	1500	8.94	2.69	50.8
26A	58-003	Stoneco	300	1.79	2.69	10.2
2NS	63-114	Highland	1150	6.95	2.65	39.0
Total Wt			2950	17.68		100.0

<----- Verify this number is 100%



Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Sieve	6AA	26A	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	99.7	100.0	100.0	99.8	0.2	0.2
3/4"	81.1	100.0	100.0	90.4	9.5	9.6
1/2"	43.9	99.3	100.0	71.4	19.0	28.6
3/8"	22.6	88.2	100.0	59.4	12.0	40.6
#4	3.3	11.5	98.9	41.4	18.0	58.6
#8	2.0	2.4	85.0	34.4	7.0	65.6
#16	1.0	1.3	66.3	26.5	7.9	73.5
#30	0.9	1.1	45.4	18.3	8.2	81.7
#50	0.8	1.0	21.0	8.7	9.6	91.3
#100	0.8	1.0	4.5	2.3	6.4	97.7
LBW	0.7	0.9	0.3	0.6	1.7	99.4

*Maximum % Retained must be above the 3/8" sieve.

*Any two adjacent sieves must equal 10% except max.,

nom. max., #100 and #200 sieves.

*% Retained must be at least 4% for each sieve except max.,

nom. max., #100 and #200 sieves.

*% Retained must be at least 4% for the 3/4" sieve when

a 1.5" max. size (nom. Max. 1.0") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations


Adjusted WF Initial Production Sample (IPS)

Coarseness Factor:	62	Workability Factor:	34	36.9
---------------------------	-----------	----------------------------	-----------	-------------

Coarseness Factor:	61
---------------------------	-----------

Workability Factor:	36
----------------------------	-----------

Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	99.3	0.7	0.7
3/4"	89.2	10.1	10.8
1/2"	70.7	18.5	29.3
3/8"	60.7	10.0	39.3
#4	44.4	16.3	55.6
#8	35.9	8.5	64.1
#16	27.3	8.6	72.7
#30	19.1	8.2	80.9
#50	7.4	11.7	92.6
#100	1.9	5.6	98.1
LBW	0.7	1.2	99.3



PREPARED BY:
 SM, LLC Technical Service

Approved BY:

Aggregate Optimization Chart

PLANT #: 12

Sample Date: 11/11/24

Concrete Grade: DM, 4500HP

Contractor: _____

Dates Test Represents: 11/12/2024 through 11/18/2024

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
6AA	71-47	Presque Isle	1755	10.73	2.62	60.4
26A	71-47	Presque Isle	0	0.00	2.62	0.0
2NS	63-115	Ray Rd	1150	6.95	2.65	39.6
Total Wt			2905	17.69		100.0

<----- Verify this number is 100%



Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336


Sieve	6AA	26A	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	98.4	100.0	100.0	99.0	1.0	1.0
3/4"	88.0	100.0	100.0	92.8	6.3	7.2
1/2"	52.8	95.4	100.0	71.5	21.3	28.5
3/8"	34.4	83.4	100.0	60.4	11.1	39.6
#4	6.3	18.9	97.6	42.4	17.9	57.6
#8	2.6	5.0	80.2	33.3	9.1	66.7
#16	2.1	2.9	64.2	26.7	6.6	73.3
#30	2.0	2.5	48.3	20.3	6.4	79.7
#50	2.0	2.3	25.4	11.3	9.1	88.7
#100	1.9	2.2	5.7	3.4	7.9	96.6
LBW	1.6	2.1	1.1	1.4	2.0	98.6

*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for the 3/4" sieve when a 1.5" max. size (nom. Max. 1.0") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Adjusted WF Initial Production Sample (IPS)

Coarseness Factor:	59	Workability Factor:	33	Adjusted WF	35.8	Coarseness Factor:	63
---------------------------	-----------	----------------------------	-----------	--------------------	-------------	---------------------------	-----------



Workability Factor:		36	
Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	99.3	0.7	0.7
3/4"	89.0	10.3	11.0
1/2"	70.3	18.7	29.7
3/8"	59.9	10.4	40.1
#4	41.9	18.0	58.1
#8	35.9	6.0	64.1
#16	27.8	8.2	72.2
#30	18.9	8.8	81.1
#50	6.3	12.6	93.7
#100	1.7	4.6	98.3
LBW	1.0	0.7	99.0

PREPARED BY:
 SM, LLC Technical Service

Approved By:

Aggregate Optimization Chart

PLANT #: p11

Contractor: _____

Sample Date: 11/11/24

Concrete Grade: DM, 4500HP

Dates Test Represents: 11/12/2024 through 11/18/2024

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
6AA	71-47	Presque Isle	1755	10.73	2.62	60.4
26A	71-47	Presque Isle	0	0.00	2.62	0.0
2NS	63-115	Ray Rd	1150	6.95	2.65	39.6
Total Wt			2905	17.69		100.0

<----- Verify this number is 100%



Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Sieve	6AA	26A	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	98.4	100.0	100.0	99.0	1.0	1.0
3/4"	88.0	100.0	100.0	92.8	6.3	7.2
1/2"	52.8	95.4	100.0	71.5	21.3	28.5
3/8"	34.4	83.4	100.0	60.4	11.1	39.6
#4	6.3	18.9	97.6	42.4	17.9	57.6
#8	2.6	5.0	80.2	33.3	9.1	66.7
#16	2.1	2.9	64.2	26.7	6.6	73.3
#30	2.0	2.5	48.3	20.3	6.4	79.7
#50	2.0	2.3	25.4	11.3	9.1	88.7
#100	1.9	2.2	5.7	3.4	7.9	96.6
LBW	1.6	2.1	1.1	1.4	2.0	98.6


*Maximum % Retained must be above the 3/8" sieve.
 *Any two adjacent sieves must equal 10% except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for each sieve except max., nom. max., #100 and #200 sieves.
 *% Retained must be at least 4% for the 3/4" sieve when a 1.5" max. size (nom. Max. 1.0") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations

Adjusted WF Initial Production Sample (IPS)

Coarseness Factor:	59	Workability Factor:	33	Adjusted WF	35.8	Coarseness Factor:	62
---------------------------	-----------	----------------------------	-----------	--------------------	-------------	---------------------------	-----------

Workability Factor: 36



Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	100.0	0.0	0.0
3/4"	95.0	5.0	5.0
1/2"	72.3	22.8	27.7
3/8"	60.4	11.8	39.6
#4	42.6	17.8	57.4
#8	36.0	6.6	64.0
#16	29.5	6.5	70.5
#30	20.3	9.2	79.7
#50	9.5	10.8	90.5
#100	3.4	6.1	96.6
LBW	1.3	2.1	98.7

PREPARED BY:
 SM, LLC Technical Service

Approved By:

Aggregate Optimization Chart

Production Gradation Report

PLANT #: P-02

Sample Date: 11/11/24

Concrete Grade: **DM, 4500HP**

Contractor: _____

Dates Test Represents: 11/12/2024 through 11/18/2024

MDOT No.: _____

Agg. Class	Pit #	Source	Weight (SSD)	ft ³	Specific Gravity	% Contribution
6AA	71-47	Presque Isle	1755	10.73	2.62	60.4
26A	71-47	Presque Isle	0	0.00	2.62	0.0
2NS	63-115	Ray Rd	1150	6.95	2.65	39.6
Total Wt			2905	17.69		100.0

<----- Verify this number is 100%



Superior Materials, LLC
 30701 W. 10 Mile Rd.
 Suite 500
 Farmington Hills, MI 48336

Sieve	6AA	26A	2NS	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	100.0	100.0	100.0	0.0	0.0
1.5"	100.0	100.0	100.0	100.0	0.0	0.0
1"	98.4	100.0	100.0	99.0	1.0	1.0
3/4"	88.0	100.0	100.0	92.8	6.3	7.2
1/2"	52.8	95.4	100.0	71.5	21.3	28.5
3/8"	34.4	83.4	100.0	60.4	11.1	39.6
#4	6.3	18.9	97.6	42.4	17.9	57.6
#8	2.6	5.0	80.2	33.3	9.1	66.7
#16	2.1	2.9	64.2	26.7	6.6	73.3
#30	2.0	2.5	48.3	20.3	6.4	79.7
#50	2.0	2.3	25.4	11.3	9.1	88.7
#100	1.9	2.2	5.7	3.4	7.9	96.6
LBW	1.6	2.1	1.1	1.4	2.0	98.6

*Maximum % Retained must be above the 3/8" sieve.

*Any two adjacent sieves must equal 10% except max.,

nom. max., #100 and #200 sieves.

*% Retained must be at least 4% for each sieve except max.,

nom. max., #100 and #200 sieves.

*% Retained must be at least 4% for the 3/4" sieve when


a 1.5" max. size (nom. Max. 1.0") aggregate is used.

Production Gradation Batch Plant Gradations Aggregate Supplier Gradations Adjusted WF Initial Production Sample (IPS)

Coarseness Factor: 59 **Workability Factor:** 33 **35.8**

Coarseness Factor: 63

Workability Factor: 35



Sieve	Cumulative % Passing	% Retained	Cumulative % Retained
2"	100.0	0.0	0.0
1.5"	100.0	0.0	0.0
1"	100.0	0.0	0.0
3/4"	95.1	4.9	4.9
1/2"	74.6	20.5	25.4
3/8"	59.3	15.3	40.7
#4	42.1	17.2	57.9
#8	35.1	7.1	64.9
#16	29.2	5.9	70.8
#30	21.9	7.3	78.1
#50	9.6	12.4	90.4
#100	2.4	7.2	97.6
LBW	0.9	1.5	99.1

PREPARED BY:
 SM, LLC Technical Service

Approved By: